

Specification Sheet

VIAVI

CX300

ComXpert

General Specifications

General	
Display	
Size	10 in (25.4 cm)
Timebase	
Accuracy	0.02 ppm (0°C to 50°C)
Aging	±1 ppm/year
Warm-up time	3 minutes: within ±0.01 ppm
Accuracy with GPS	±25 ppb (GPS Lock) ±50 ppb (Hold over 72 hours)
External Reference	10 MHz
RF Generator	
Frequency	
Range	100 kHz to 3GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Resolution	1 Hz
Accuracy	Same as timebase
Output Level	
RF Duplex Port Range	-140 dBm to -30 dBm (10 MHz to 1 GHz); -37 dBm for AM and Complex modulation
RF Output Port Range	-130 dBm to +17 dBm (10 MHz to 1 GHz); +10 dBm for AM and Complex modulation
Resolution	0.1 dB
Accuracy	±1.0 dB (output level > -120 dBm, 1 MHz to 6 GHz) ±2.0 dB (output level ≥ -130 dBm, 1 MHz to 6 GHz) ±1.0 dB typical
Bandwidth	100 MHz
VSWR	
RF Duplex Port	≤11 (1 MHz to 1 GHz); <1.2 (1 GHz to 6 GHz)
RF Output Port	≤1.4 (1 MHz to 1 GHz); <1.5 (1 GHz to 6 GHz)
Spectral Purity	
Phase Noise	-112 dBc/Hz at 10 kHz offset at 500 MHz -110 dBc/Hz at 10 kHz offset at 1000 MHz
Harmonics	-35 dBc
Non-Harmonics	-45 dBc

Residual AM	<0.1% rms
Residual FM	<3 Hz rms 300 Hz to 3 kHz
Analog Modulation	
Modulation	
Modes	AM, FM, PM, SSB
Frequency Range	20 Hz to 20 kHz
Distortion	<1% THD
AM	
Range	0% to 100%
Resolution	0.1%
Accuracy (internal source)	≤±5% of settings
FM	
Range	0 Hz to 100 kHz
Resolution	1 Hz
Accuracy (internal source)	≤±2.5% of setting with frequency response of ±0.5 dB 20 Hz to 10 kHz
PM	
Range	0 rad to 6.3 rad
Resolution	0.1 rad
Accuracy	<±2.5% of setting with frequency response of ±0.5 dB 20 Hz to 10 kHz
SSB	
Modulation frequency	30 Hz to 20 kHz
Carrier suppression	>70 dB
Sideband suppression	>60 dB
Internal Modulation Sources	
Number of sources	3

Sources	
Waveforms	Sine, Square, DTMF, CTCSS, DCS, Two-Tone, Tone Remote, Tone Sequential
Sine Wave	
Range	20 Hz to 20 kHz
Resolution	0.1 Hz
Square Wave	
Range	20 Hz to 20 kHz
CTCSS tone	Tone 1 (67) to Tone 50 (254.1) Hz
Distortion	THD <1.0%
Frequency Response	Level flatness ≤ 0.5 dB 20 Hz to 10 kHz
RF Receiver	
Frequency	
Range	9 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Maximum Input Level	
RF Input Port Maximum Input Level	+27 dBm (500 mW) max preamp and frequency ≥ 1 MHz +13 dBm (20 mW) max preamp on or frequency <1 MHz
RF Duplex Port Maximum Input Level	+47 dBm (50 Watts) continuous, + <35°C +51 dBm (125 Watts) Cyclical (Max "ON" of 30 sec and Min "OFF" for 90 sec) for power levels >50 Watts
Shutdown	Alarm sounds (no auto shutdown)
VSWR	
RF Duplex Port	≤ 1.2 (100 kHz to 1 GHz)
RF Input Port	≤ 1.6 (100 kHz to 1 GHz) with 10 dB input attenuation
Harmonic Response	
Spurious Response	Input related ≤ -65 dBc typical Non-input related ≤ -95 dBm typical
Phase Noise	-112 dBc/Hz at 10 kHz offset at 500 MHz -110 dBc/Hz at 10 kHz offset at 1000 MHz
Dynamic Range	$2/3 * (TOI - DANL) = 109$ dB
TOI	+20 dBm (0 atten), >+1 dBm (preamp), 1 MHz to 1 GHz
DANL	1 Hz RBW @ 1 GHz; <-144 dBm (0 atten), <-162 dBm (preamp)
Sensitivity	
Analog	10 dB SINAD, <-105 dBm with preamp (300 Hz to 3 kHz audio filter, 2.5 kHz FM deviation, 12.5 kHz IF BW)
Bandwidth	100 MHz (wideband VSA), 8 MHz (narrowband)
RF Bandpass Filter (IF Filters)	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, 300 kHz
Power Meter	
Frequency	
Range	100 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Measurement Modes	RMS, average RMS, minimum, maximum

Bandwidth	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, and 300 kHz
Level	
RF Duplex Port	-20 dBm to +51 dBm
RF Input Port	-60 dBm to +10 dBm
Accuracy	
RF Duplex Port	± 0.4 dB (1 MHz to 1 GHz); ± 0.6 dB (1 GHz to 6 GHz)
RF Input Port	± 0.8 dB (1 MHz to 1 GHz), ± 0.9 dB (1 GHz to 6 GHz)
RF Error Meter	
Frequency	
Range	100 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Resolution	1 Hz
Accuracy	Frequency Reference
Input Level Range	
RF Duplex Port	-20 dBm to 51 dBm
RF Input Port	-60 dBm to +17 dBm (-80 dBm to -20 dBm w/ pre-amp)
Analog Demodulation Measurements	
FM	
Modes	RMS, $RMS * \sqrt{2}$, +PK, -PK, $\pm PK/2$
Measurement Range	0 Hz to 75 kHz
Accuracy	$\pm 1.0\%$ for rate ≥ 1.5 kHz and ≤ 3 kHz $\pm 2.0\%$ otherwise
FM Distortion	$\pm 0.5\%$ for rate ≤ 3 kHz $\pm 1.0\%$ otherwise
Residual FM	≤ 3 Hz (300 Hz to 3 kHz) and frequency <1 GHz
AF Frequency Range	10 Hz to 20 kHz
AM	
Modes	RMS, $RMS * \sqrt{2}$, +PK, -PK, $\pm PK/2$
Measurement Range	0% to 100%
Accuracy	$\pm 1.0\%$ for rate ≥ 1.5 kHz and ≤ 3 kHz $\pm 2\%$
AM Distortion	$\pm 0.5\%$ for rate ≤ 3 kHz $\pm 1.0\%$ otherwise
AF Frequency Range	10 Hz to 20 kHz
Residual AM	<0.1% (300 Hz to 3 kHz)
PM	
Range	0 radians to 6.3 radians
Resolution	0.01 rad for ≤ 5 rad 0.1 rad for >5 rad
Accuracy	$\pm 2.0\%$, $\pm 1.0\%$ (rate 1.5 kHz to 3 kHz)
SSB	
Modes	SSB-USB, SSB-LSB
Measurement Range	Frequency error, Power (RMS), Power (PEP)

Audio and Demodulation Meters	
Distortion Meter	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0% to 100%
Accuracy	<3% of reading +0.1% distortion, 1% to 20%
SINAD Meter	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0 dB to 63 dB
Accuracy	<±1 dB
S/N Meter	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0 dB to 63 dB
Accuracy	<1 dB
AF Counter	
Frequency Range	50 Hz to 10 kHz
Accuracy	Timebase ±1 Hz
AF Tones Analyzer	
Modes	DTMF, DCS, CTCSS, Two-Tone, Tone Sequential, Tone Remote
Audio Level Meter	
Input Impedance	100 k Ω , 600 Ω
Level	
Range	0 Vrms to 30 Vrms
Audio Analyzer	
Frequency Range	DC to 100 kHz
Frequency Resolutions	0.8 Hz to 2.4 Hz RBW
FFT Windows	Flat top, rectangular, Hamming, Hann, Blackman-Harris
Level	
Range	50 mVrms to 30 Vrms
Accuracy	±5% (Audio) ±1% (DC)
Audio Filters	
Lowpass	300 Hz, 3 kHz, 3.4 kHz, 5 kHz, 15 kHz, 20 kHz
Highpass	20 Hz, 50 Hz, 300 Hz
Other	C-MSG, CCITT, A-Weighted, C-Weighted
De-emphasis	75 μ s, 750 μ s
FFT / Channel Analyzer	
Span	2 kHz to 8 MHz
IF Bandwidth	10 MHz
RBW	1 Hz to 50 kHz
Detector	Normal, positive peak, negative peak, sample, average (RMS)

Accuracy	RF Duplex Port: ±0.7 dB (1 MHz to 1 GHz), ±1 dB (1 GHz to 6 GHz) for level >-10 dBm RF Input Port: ±1.0 dB (1 MHz to 1 GHz), ±1.1 dB (1 GHz to 6 GHz) for level >-50 dBm
Spectrum Analyzer	
Frequency Range	9 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
RBW Range	100 Hz to 5 MHz
Span Range	0 Hz to (9 kHz to max frequency of each band)
VBW Range	100 Hz to 5 MHz
Sweep Time Range	0.4 ms to 1000 s
Spurious Free Dynamic Range	≥80 dB
Display Range	1 dB/div to 20 dB/div with 10 divisions
Trigger	Free run, external
DANL	<-142 dBm (0 atten), <-162 dBm (preamp)
Zero Span Analyzer	
Sweep Time	
Range	24 μ s to 200 s
Tracking Generator	
Output Ports	RF Output Port, RF Duplex Port
Level	
Range	Same as RF Generator
Accuracy	Same as RF Generator
I/Q Recorder	
Sample	
Length	4 Msamples
Rate	Variable to support up to 100 MHz of analog bandwidth
Trigger	
Trigger Source	Free run
AF Generator	
Output	
Impedance	<4 Ω
Max Output Current	100 mA
Frequency	
Range	0 Hz to 100 kHz
Resolution	0.1 Hz
Accuracy	Timebase
Level	
Range	0 Vpk to ±8 Vpk into 600 Ω
Accuracy	±2% (level ≥200 mV and frequency from 20 Hz to 20 kHz)
Distortion	
THD+N	<-75 dB for frequency 1 kHz and level 1 Vrms
AF Composite Signals	Sine, Square, DTMF, DCS, Two-Tone, Tone Remote, Tone Sequential

Oscilloscope	
Display	
Traces	2
Markers	6
Horizontal	
Sweep per div	20 μ s to 1 s/div
Accuracy	<2%
Vertical	
Range	0.1 mV/div to 20 V/div
Accuracy	<5%
Bandwidth	100 kHz
Input Range	20 mV to 30 Vrms (42.4 Vpk)
Coupling	AC, DC
Input Impedance	300 Ω , 600 Ω , 100 k Ω single ended, \pm 1% shunted by <300 pF 200 k Ω differential, \pm 8%
Trigger	
Modes	Single, Normal, Automatic, Free run
Digital	
Modes	P25, P25 Phase 2
P25 Measurements	
Accuracy	
Modulation Fidelity	<5% of reading (2.5% to 12%)
Symbol Deviation	\pm 1%
Frequency Error	Timebase \pm 0.5 Hz
Symbol Rate Error	Timebase \pm 0.1 ppm

Environmental / Physical

Weight	15 lbs (6.8 kg)
Temperature, Not Operating	-40°C to +71°C Note: Battery must not be subjected to temperatures below -20°C, nor above +60°C
Temperature, Operating	0°C to 50°C (battery removed)
Relative Humidity	95% RH (non-condensing)
Altitude	4600 m
Vibration	MIL-PRF-28800F Class 3
Shock, functional	MIL-PRF-28800F Class 3
Bench handling	MIL-PRF-28800F Class 3
Transit Drop	MIL-PRF-28800F Class 3
Battery	
Type	Lithium Ion, 14.4 V, 6.8 Ah
Operating Time	2.3 hours typical with 2 batteries
Battery Charging Limits	0°C to 45°C (32°F to 113°F) \leq 85% RH
Compliance	
EMC	IEC/EN 61326-1:2006, CISPR11:2009 +A1:2010
Safety	EN 61010-1, 3rd Edition



Contact Us +1 800 835 2352
AvComm.Sales@viavisolutions.com

To reach the VIAMI office nearest you, visit
viavisolutions.com/contact

emitec
industrial

Emitec Messtechnik AG
Birkenstrasse 47
6343 Rotkreuz

+41 41 748 60 10
info@emitec.ch
www.emitec-industrial.ch

Emitec Group
#1 In Test & Measurement, worldwide.